



ADVANCED CLEAN™ 3.0 SPALET® BIDET SEAT

Questions and Answers

Warranty

What is the warranty?

There is a three year warranty on all parts of the SpaLet for residential applications and a two year warranty on parts for commercial applications. Terms and conditions apply.

Install

Is a professional plumber required for installation?

The bidet seats itself is very simple to install and much like a regular toilet seat with the addition of a water hose and tee connector. You can have a professional plumber do it, but many people prefer to install it themselves.

What type of power is needed?

AC120V GFCI outlet. The seat consumes 1300W.

What type of water pressure is needed?

Minimum Inlet Water Pressure is 7.25 psi Flow Pressure.

Maximum Inlet Water Pressure is 108.7 psi Hydrostatic Pressure.

How much power is consumed by the heated seat?

The heating power is 45W.

Does this bidet seat fit my toilet?

The bidet seat fits most elongated toilets; please refer to the fit chart in the installation manual.

Do you need to buy anything else for installation?

Items needed for installation include standard household tools such as an adjustable wrench, Phillips and flat head screw driver.

Components

What comes with the product?

The following parts are included in the product:

- Seat unit (seat ring, seat lid and power cord)
- Mounting plate
- Manual
- Mounting bolts, brackets, washer, and bushings (2 pieces each)
- Seat unit water supply hose (with 2 clips)
- Remote control and remote holder
- Junction fitting
- Batteries
- Wood screw
- Plastic anchors

Is the remote included in the product?

The remote and batteries are included with the purchase of the Advanced Clean 3.0 SpaLet bidet seat.

Dimensions

What is dimension of the product?

The dimension of the product is 16-1/4" (413 mm) (W) x 21-5/16" (541 mm) (D) x 4-1/16" (104 mm) (H)

What is the size of the seat opening??

The inner diameter of the seat is 7-15/16" (202 mm) wide and 11-5/8" (295 mm) long.

How long is the power cord?

Effective length 39" or 990 mm.

Functions and Features

How does the self-cleaning nozzle work?

Once the user presses the spray function, the automatic self-cleaning nozzle function rinses the nozzles prior to opening the nozzle shutter door and extending the nozzles. This function cleans the nozzle and surrounding area before and after use of the back cleansing, back cleansing – mild and front cleansing.

What is a nozzle shutter?

The nozzle shutter is the door that covers the nozzles. This provides an additional level of hygiene by preventing waste or debris from contacting the nozzle tips.

What are the main features?

- Heated seat (5 temperature levels)
- Dual, adjustable, self-cleaning water sprays for independent front and back cleansing
- Adjustable water control settings: pressure (6 levels), temperature (5 levels), massage and oscillation
- Air dryer (3 temperature level)
- Air Shield Deodorizer controls and reduces odors inside the bowl
- Pre-Mist for added cleanliness
- Instant heat for on demand warm water

How long is the spray cycle?

Both the back and front cleansing automatically stops after 2 minutes but can manually be stopped by pressing the Stop button at any time.

How much water is used during the spray cycle?

The spray volume used is as follows:

- Back Cleansing: 14.54 oz./min (6-level adjustment by pulse method) at water supply pressure of 29 psi
- Back Mild Cleansing: 15 oz./min (6-level adjustment by pulse method) at water supply pressure of 29 psi
- Front Cleansing: 15 oz./min (6-level adjustment) at water supply pressure of 29 psi

How long is the drying cycle?

Dryer function automatically stops after 4 minutes but can manually be stopped by pressing the Stop button at any time.

How many different water temperature settings are available?

5 different levels of water temperature settings are available.

How many seat temperature settings are available?

5 different levels of water temperature settings are available.

How many dryer temperature setting is available?

3 different levels of water temperature settings are available.

How many water pressure settings are available?

6 different levels of water temperature settings are available.

What are the different spray patterns?

6 different spray patterns: Back Cleansing, Back Oscillation, Back Massage, Back Mild Cleansing, Front Cleansing, Front Oscillation.

What is Oscillation?

Oscillation spray moves the nozzles forwards and backwards continuously allowing for a wider area to be cleansed.

What is the temperature of the heated seat?

Depending on the use of the ECO mode, the temperature of the seat can vary. If High Efficiency Power Savings is being used the seat will be at room temperature and begin to power up only after the user initiates using the bidet seat. During regular use with or with ECO mode the temperature ranges from approx. 82.4°F to 96.8°F.

What is the temperature of the water?

The water temperature has a range of: Approx. 89.6°F to 104°F (6-level setting including OFF).

What is the temperature of the air dryer?

The temperature has a range of approx. 104°F to 131°F.

Does this have an automatic seat? Slow-close seat?

The Advanced Clean™ 3.0 SpaLet® bidet seat does have a slow-close seat and lid for user convenience but does not have an automatic open/close lid.

How does the bidet work?

The user must sit on the seat to depress the seat sensor to allow the bidet functions to work. Then with the touch of a button, the self-cleaning nozzles extend from behind the nozzle shutter, under the seat to deliver soothing warm water for cleansing.

How long does the heated seat stay warm?

You can set the seat to be warm all the time by NOT using the ECO function. If you use the eco power saving mode it shuts the water and seat heater off for 8 hours then restores the power. If High Efficiency Power savings is used it turns the water and seat heater off until the product is back in use.

Explain the eco function, how does it work?

It reduces power consumption by turning off the seat heater for 8 hours. The power settings are automatically restored after 8 hours. To use this feature press the ECO button on the remote. There is also a secondary High Efficiency Power Savings that lowers the water temperature between uses by pressing the nozzle cleaning and power savings buttons for 2 seconds or more; a light indicator flashes once activated.

How much electricity does this consume?

Advanced Clean 3.0 SpaLet bidet seat has a rated power consumption of 1300W.

How much electricity does the dryer consume?

The dryer consumes 340W.

How does the heated water supply work, where do I get the warm water from?

The incoming water is transferred through an instant water heating element that keeps the water warm on a continuous basis during use.

How long does the heated water last for?

The heated water is available on demand. It will not run out.

Where does the water come from that the bidet function uses?

The clean water comes from the incoming water supply line. Tank water is NOT used for the bidet function.

Does this toilet have a nightlight?

No, the 8012A AC 2.0 and 8013A AC 1.0 bidet seats do not have a nightlight.

Is there a child lock out feature?

There is no specific child lock out feature but we do have a seat sensor that must be depressed to operate the bidet function. The bidet will not operate unless both the sensor is engaged and a user initiates a cleansing cycle simultaneously.

What is Air-Shield Deodorizer?

The air is circulated within the toilet bowl to create a powerful deodorizing effect. Circulating air prevents odors from escaping, which controls and reduces odors inside the bowl.

What is Pre-Mist?

Pre-Mist wets the bowl surface to reduce waste buildup. It activates once seated and the water will be sprayed on to the bowl for approximately 6 seconds.

How to Use

How do you adjust the nozzles for a better aim?

Our Advanced Clean™ 3.0 SpaLet® bidet seat has 5 levels of nozzle position adjustment. These are easily changed by pressing the nozzle position arrows on the user-friendly remote.

What type of maintenance is required/recommended?

- Cleaning of the seat can be achieved by using a cloth and a non chlorinated cleaner.
- Changing or cleaning the nozzle tips: Press the 'Nozzle Cleaning' button for 2 seconds to extend the nozzles then pull the nozzle tips out. Push the tips back onto the nozzles once cleaned.
- Cleaning the nozzle shutter.
- Cleaning the deodorizer filter: Disconnect the power supply, shut the water valve off, remove the seat, pull the screen from under the seat out, clean the filter with a small brush or toothbrush, re-install the screen, re-install the seat, plug the seat in, turn on the water supply.
- Winterizing the seat: Only needed if the seat will not be used and the temperature of the house is lowered. Unplug the unit, turn off the water supply, depress the seat sensor or sit on the seat and activate the wash cycle to drain the tank, press the seat release button to remove from the toilet, remove the strainer on the left side of the unit, tilt the seat and completely drain the water from the seat, reattached the strainer, remove the drain plug located on the bottom of the seat, tilt the seat forward and drain, reinstall the drain plug, reinstall the seat.
- Changing the batteries.

Is this product suitable for children?

When small children are using this product, ensure that the proper operating procedures are followed at all times to ensure the user's safety.

Can you customize the settings?

Yes, you can customize your cleaning experience by adjusting the water control settings, water pressure settings (6 levels), water temperature settings (6 levels) plus the massage and oscillation features to maximize your cleansing experience.

Can you save the customized settings?

No, You cannot save customized user settings as in user 1, user 2 but the settings will stay the same until they are manually changed.

How do I clean this product?

You can clean the seat by using soft cloth and non-chlorinated cleaner.

Do I have to mount the remote?

No, You do not have to mount the remote if you do not have an accessible wall to mount this on but it is recommended to do so for ease of use if a wall is located within arms reach of the toilet.

Can you turn off the deodorizer?

Yes, you can turn the deodorizer off by pressing the water temperature and nozzle cleaning buttons simultaneously for 2 seconds.

How long does the deodorizer run for?

Deodorizing starts when a person sits on a seat and will run for 1 minute once the user stands up and releases the seat sensor.

How long should I use a bidet?

Duration of the spraying function can last up to 2 minutes and the user can stop the spray cycle at any time by pushing stop. The cycle will automatically stop at 2 minutes but can be extended up to 6 minutes using the massage function or pressing the spray cycle again. Duration for individual use will vary depending on personal cleansing needs.

Other**Where is it manufactured?**

The Advanced Clean™ 3.0 SpaLet® bidet seats are manufactured in Japan.

What is the weight limit for this SpaLet bidet seat?

The seat is approved up to 264 pounds.

Could you use it outside North America?

This product is designed for use in the USA and Canada. Please refer to the product specifications chart in the installation manual for electrical and water requirements.